

King Steps

Ergonomic ladder, with parapet, made of all anodized aluminium. Portable, collapsible, self-supporting. Suited to most different appliances: industrial, military, professional, warehouses, office and home. Unvaried design since 1986: anodized aluminium, red synthetic foam pads, exceeds OSHA and EN ratings. Comes in completely anodized aluminium as well as in insulating material as well as in dissipative ESD material.

Please click on the image for a larger picture



Portable and collapsible stairway 2-4 treads
with 0.80 m high parapet, for free standing appliances up to 2.75 m.



Portable and collapsible stairway 4 treads only
Standing height 93 cm / 36 in Top height of Rail 200 cm / 79 in

Tread layers "Red Scarlet":

RAL 3020

21 x 34 cm / 8 x 13 in

Self-adhesive polyethylene foam

- Temperature resistant -10°C +90°

- traction 22 Kg/cm

- density 200 Kg / cubic meter

- non absorbs liquids: humidity 2%

- shore 55/60

- built to HACCP Standard

- UV-resistant

- ozone 168H/200 pphm

- hardness 10% - 4,5 Kg/cm

- safe for children >3 years: EN 71

- use high pressure water cleaner
without detergents**Tread Layers "Cristall":**

Semi-transparent

21 x 34 cm / 8 x 13 in

Self -adhesive polypropylene

Duty Rate

250 kg / 550 lb

Anodized aluminium

Anodizing seals the ladder from oxidation and corrosion; it makes cleaning of the surface easier and permits the ladder to be used in many sectors:

- office, furniture and domestic appliances

- shops and food markets

- slaughtering, chemical, food and drug industry

- freezing and clean rooms

- catering, hospital and laboratories

- galleries, churches and libraries

- shelves and deposits

- helicopters and riding schools

- military and marine specs.

Non-conductive Aluminium **KingStar**Dissipative Aluminium **KingStep ESD**

	KingStep 2	KingStep 3	KingStep 4	KingStep 4 Rail
working height	2.30 m	2.50 m	2.75 m	2.75 m
	7.545 ft	8.202 ft	9.022 ft	9.022 ft
weight	6.50 kg	8 kg	10 kg	14 kg
	14.33 lb	17.637 lb	22.046 lb	30.864 lb
n° of treads	2	3	4	4
distance of treads	23 cm	23 cm	23 cm	23 cm
	9 in	9 in	9 in	9 in
surface of tread	23 x 36 cm	23 x 36 cm	23 x 36 cm	23 x 36 cm
	9 x 14 in	9 x 14 in	9 x 14 in	9 x 14 in
	1.52 m	1.85 m	2.16 m	2.46 m

height closed	1.52 m	1.85 m	2.16 m	2.46 m
height open	86 cm	80 cm	93 cm	83 cm
standing height	18 in	28 in	37 in	37 in
	152 x 48 x 7 cm	185 x 48 x 7 cm	216 x 48 x 7 cm	244 x 54 x 7 cm
	60.166 x 19 x 3 in	73.229 x 19 x 3 in	85.499 x 19 x 3 in	97.374 x 21.374 in

OPEN :

1. Face colored tread layers
2. Rotate upper tread



CLOSE :

Rotate upper tread

Merlin
Industrial Products Ltd

Kingsley Close, East Way
Lee Mill Industrial Estate
Ivybridge, DEVON PL21 9LL
United Kingdom
Call 0845 124 9955
Fax 0845 125 9955

sales@mipi.org.uk