

Chemstor® - CS6

Backed by a 20 year structural guarantee*

The base is manufactured from 3mm mild steel sheet with pressed ribs. All the corner posts, main rails and cross members are from rolled hollow section. The roof is pressed as required with suitable bracing and fully welded around the perimeter, while the back, side and door panels are pressed from 2mm mild steel sheet and corrugated where required. The bulkhead door is 1250mm wide and fitted with single cam door gear which is secured with a padlock (not supplied). Inside the unit there are three sets of double shelves and the fully seam welded sump is fitted with a removable galvanised grid mesh deck. High and low level louvre vents complete with flame arrestor mesh are fitted as standard and the unit is shot blasted before being painted.

*Details available on request



Size	5920mm L x 2440mm W x 2658mm H at the highest point
N° of containers	108 x 25ltr including the deck area under the shelves
Sump capacity	2196ltr
Colour	Green RAL 6029
Tare weight	2200kg

Note: This unit will be delivered by an articulated vehicle, therefore please ensure that a vehicle of this size can access your premises before ordering and advise us accordingly.



Merlin Industrial Products Ltd

Kingsley Close, Lee Mill Industrial Estate

Ivybridge, Devon PL21 9LL

United Kingdom

Call: +44(0)1752 690 622

Fax: +44(0)2081 962 223

WWW: www.merlin-industrial.co.uk

Email : info@merlin-industrial.co.uk