

Steptek Easy Rise Range with Handlock Anchorage



Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation. Welded steel tube and bar construction, fitted with hand lock anchorage. When locked the front feet rest firmly on the floor, feet fitted with protective plastic floor pads.

48 degree slope for extra safety and comfort. Designed to allow user to descend the steps facing forward. 760mm tread width.

Finish: All steelwork red epoxy finish. Wheels: Front 2 swivel castors with 100mm diameter rubber tyred wheels with roller bearings. Rear 2 axle mounted 200mm diameter wheels with rubber tyres and roller bearings.

S613



Call Merlin Industrial for optional extras.




**British Standard
Safety Steps**



KM 608967
BS EN 131-7

Tread width 760mm
Platform W x D: 760 x 400mm



Number of Treads inc Platform	Average Working Height mm	Platform Height mm	Overall Dimension (H x W x D) mm	R/Rubber Treads Order Ref	Kg	Anti-Slip Treads Order Ref	Kg	Expamet Treads Order Ref	Kg	Punched Treads Order Ref	Kg	Aluminium Treads Order Ref	Kg
5	2650	1150	2110 x 980 x 1400	S601	80	S611	80	S621	80	S631	78	S641	82
6	2880	1380	2340 x 980 x 1600	S602	88	S612	88	S622	88	S632	86	S642	91
7	3110	1610	2570 x 980 x 1800	S603	96	S613	96	S623	96	S633	94	S643	99
8	3340	1840	2800 x 980 x 2000	S604	104	S614	104	S624	104	S634	102	S644	108
9	3570	2070	3030 x 980 x 2200	S605	112	S615	112	S625	112	S635	110	S645	117
10	3800	2300	3260 x 1150 x 2400	S606	132	S616	132	S626	132	S636	130	S646	138
11	4030	2530	3490 x 1150 x 2600	S607	142	S617	142	S627	142	S637	140	S647	149
12	4260	2760	3720 x 1150 x 2800	S608	152	S618	152	S628	152	S638	150	S648	160

*10 tread and above supplied in 2 halves for transport purposes. Refer to page 25 for optional extras

