


Street Furniture



- Easily installed
- Four fixing options
- Choice of four diameters
- Stylish brushed finish
- Polished cap



CHICHESTER Stainless Steel Bollards

The **CHICHESTER** range of Stainless Steel Bollards are manufactured from brushed stainless steel with polished top caps, ensuring a high quality finish for many years, and are to be found in use around public & commercial buildings, retail parks, business parks, schools, public spaces, supermarkets etc.

Produced in seamless 304 quality stainless steel for durability they can be supplied with chain eyes (our Stainless Steel Chain is ideal for use with the **CHICHESTER** – see page 82). Please advise if installation is on a coastal site so that the appropriate grade can be supplied.

Optional extras:
For that finishing touch matching stainless steel collars are available for 60 and 76mm Ø models.

Installation method and height	Ø x Wall thickness (mm)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
Sub-Surface Fix - Permanent 900mm Above surface 300mm Below surface	60 x 2	7	167.18.689	15 / 20 days
	76 x 2	9	167.17.883	
	101 x 2	10	167.50.816	5 / 10 days
	114 x 2	12	167.50.320	
Surface Fix 900 Above surface	60 x 2	6	167.18.490	15 / 20 days
	76 x 2	8	167.16.483	
	101 x 2	10	167.50.262	5 / 10 days
	114 x 2	12	167.50.390	
Removable – with Triangular key (complete with ground socket) 900mm Above surface 300mm Below surface	60 x 2	7.5	167.18.736	15 / 20 days
	76 x 2	9	167.18.723	
	108 x 2	10.5	167.13.750	
Removable – with Cylinder lock (complete with ground socket) 900mm Above surface 300mm Below surface	76 x 2	9	167.14.189	15 / 20 days
	108 x 2	10.5	167.15.768	
Removable – with Padlock (not supplied) Complete with ground socket (galvanised) 900mm Above surface 300mm Below surface	101 x 2	12	167.50.450	5 / 10 days
	114 x 2	14	167.50.162	
Removable – with Padlock (not supplied) Complete with ground socket (Stainless Steel) 900mm Above surface 300mm Below surface	101 x 2	12	167.50.711	5 / 10 days
	114 x 2	14	167.50.695	
Ground Collars – Stainless Steel	60	0.3	167.14.049	15 / 20 days
	76	0.4	167.18.323	
Triangular key – please order separately		0.2	130.12.326	1 / 2 days
Surface fixing bolts 12/100 (3 required per post-surface fix type)		0.2	109.17.393	
Chain eyes – please ask for details				15 / 20 days



- Easily installed
- Choice of two diameters
- Three fixing options
- Stylish brushed finish
- Polished 45° cap



CHICHESTER 45 Stainless Steel Bollards

The **CHICHESTER 45** range of Stainless Steel Bollards are manufactured from seamless brushed 304 quality stainless steel with an attractive 45° polished cap for that extra styling touch. As with the **CHICHESTER** range please advise if the installation is on a coastal location so that we can select the correct grade of stainless steel.

Produced in two diameters and three fixing methods to suit a wide range of requirements.

Installation method and height	Ø x Wall thickness (mm)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
Sub-Surface Fix - Permanent 900mm Above surface 300mm Below surface	101 x 2	10	167.50.731	15 / 20 days
	114 x 2	12	167.50.195	
Surface Fix 900 Above surface	101 x 2	10	167.50.236	
	114 x 2	12	167.50.575	
Removable – with Padlock (not supplied) Complete with ground socket (Galvanised) 900mm Above surface 300mm Below surface	101 x 2	10	167.50.125	
	114 x 2	12	167.50.391	
Removable – with Padlock (not supplied) Complete with ground socket (Stainless Steel) 900mm Above surface 300mm Below surface	101 x 2	10	167.50.432	
	114 x 2	12	167.50.551	
Surface fixing bolts 12/100 (3 required per post-surface fix type)		0.2	109.17.393	1 / 2 days

Street Furniture



- Easily installed
- Strong inner core
- Choice of two diameters and styles
- Strong steel inner core

CHICHESTER Anti-ram Stainless Steel Bollards

Where style combined with strength is required the **CHICHESTER** Anti-ram Stainless Steel Bollard range provides the perfect answer. The bollard is supplied in two elements – a galvanised mild steel inner core which is hidden within a seamless stainless steel cover. They are supplied in two styles one with a semi-domed polished cap and one with a 45° polished cap. They can be installed to protect vulnerable entrances, windows etc. and will match seamlessly in with a run of standard CHICHESTER Stainless Steel Bollards.

Please note due to their specific purpose these bollards are for sub-surface installation only.



Inner steel core

Installation method and height	Ø (mm)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
Sub-Surface Fix – Permanent Semi-domed Cap 900mm Above surface 300mm Below surface Inner steel core – 600mm Below surface	101	17	167.50.101	10 / 15 days
	114	19	167.50.034	
Sub-Surface Fix – Permanent 45° Cap 900mm Above surface 300mm Below surface Inner steel core – 600mm Below surface	101	17	167.50.206	
	114	19	167.50.352	